

Description: Chlorinated heavy weight flock lined natural/synthetic rubber blended gloves

- Features & Benefits:
- \* A blend of natural and synthetic rubber
  - \* Anatomically shaped for comfort
  - \* Pure cotton lining to absorb perspiration
  - \* Anti-slip pattern for good grip in wet and dry conditions
  - \* Beaded cuff to improve tear resistance during donning and removal and help prevent droplets from travelling beyond the glove length
  - \* Bacteriostatic and fungistatic additives
  - \* Chlorinated for improved chemical resistance
  - \* Low in soluble proteins
  - \* Ingredients comply with FDA regulations for food contact (Blue only)

Applications: Agriculture, Chemical Industry, Food Processing, Facility maintenance

Elastomer: Natural/Synthetic blended rubber

Thickness: 0.70 +/- 0.07 mm

Lining: Flocklined

Former: Picot, CIQ

Exterior: Finished smooth

Cuff Types: Bead rolled

Treatments: Chlorinated

Colours: Blue B2, Yellow Y1

AQL - Critical: 1.5

Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016, EN 388:2016+A1:2018 and EN ISO 21420:2020

Conforms to:

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6-6.5	194	180	242	310
	7-7.5	203	188	246	310
	8-8.5	211	201	260	310
	9-9.5	229	222	266	310
	XL	246	235	290	310
		Circumference in mm, +/- 5 mm		Tol. +/- 10 mm	

Shelf Life 3 Years

Protection against Chemical hazards	Performance	Degradation %
EN 374-1/TYPE A		
* Methanol (A)	Level 3	13.5
* Sodium hydroxide 40% (K)	Level 6	-2.4
* Sulphuric acid 96% (L)	Level 4	52.0
* Nitric acid 65% (M)	Level 6	27.3
* Acetic acid 99% (N)	Level 3	38.4
* Hydrogen peroxide 30% (P)	Level 6	11.1
* Formaldehyde 37% (T)	Level 6	-0.2

Note: Printed copies are valid only on the date printed

Printed Date: 28-Nov-2023

Revision:4

Published Date: 28-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964


Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

**Protection against Mechanical hazards** **Performance**

<p>EN 388</p> 	<ul style="list-style-type: none"> <li>* Abrasion resistance</li> <li>* Blade cut resistance</li> <li>* Tear resistance</li> <li>* Puncture resistance</li> <li>* TDM cut resistance</li> </ul>	<p>Level 3</p> <p>Level 1</p> <p>Level 2</p> <p>Level 1</p> <p>X</p>
---	---	--

**Protection against Micro-organisms risk** **Performance**

<p>EN 374-5</p> 	<ul style="list-style-type: none"> <li>* Protection against bacteria and fungi</li> <li>* Protection against viruses</li> </ul>	<p>Pass</p> <p>n/a</p>
---	---	------------------------