

Description: Fabric supported fully coated natural rubber gauntlet with crinkled palm

- Features & Benefits:
- \* Two piece liner without seams in the working area eliminates hand irritation
  - \* Anatomically shaped to provide good fit
  - \* Cotton interlock liner absorbs perspiration and adds to comfort
  - \* Crinkled palm enhances protection and grip
  - \* Durable and washable
  - \* Extended gauntlet cuff to protect forearm
  - \* Fully coated for extra protection
  - \* Liquid proof for use in wet conditions
  - \* Compliant with (EC) No. 1935/2004 & EU 10/2011 (Blue,Orange,Green)



Applications: Deep Sea Fishing, Forestry & Timber, Glass & Metal Industry, Quarrying

Elastomer: Natural rubber

Thickness: 1.80 +/- 0.15 mm

Lining: Interlock

Former: Plain CIII

Exterior: Crinkled finish on palm

Cuff Types: Gauntlet

Treatments:

Colours: Blue B32, Green G4, Natural N1, Orange O3

AQL - Critical: 1.5

Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 388:2016+A1:2018, EN 374-5 : 2016, EN ISO 21420:2020, EN 407 : 2020 and EN 511:2006

Conforms to: ASTM D4679 of 2021

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6	208	216	274	300
	7.5 (M)	222	228	288	300
	8.5 (L)	234	240	296	300
	9 (L+)	242	254	304	300
	10 (XL+)	252	268	308	300
	11 (XXL+)	264	272	310	300

Circumference in mm, +/- 5 mm      Tol. +/- 10 mm

Shelf Life 3 Years

EN 374-4

#### Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1



* Methanol (A)	Level 6	-5.9
* Sodium hydroxide 40% (K)	Level 6	-4.1
* Sulphuric acid 96% (L)	Level 4	-101.7
* Nitric acid 65% (M)	Level 5	-92.2
* Acetic acid 99% (N)	Level 4	-62.1
* Hydrogen peroxide 30% (P)	Level 6	-48.2
* Formaldehyde 37% (T)	Level 6	-10.6

Note: Printed copies are valid only on the date printed

Printed Date: 04-Sep-2024

Revision: 12

Published Date: 12-Jul-2024

\* Hydrofluoric acid 40% (S)

Level 6

X

**Protection against Mechanical hazards****Performance**

EN 388



- \* Abrasion resistance
- \* Blade cut resistance
- \* Tear resistance
- \* Puncture resistance
- \* TDM cut resistance

Level 3  
Level 1  
Level 2  
Level 1  
X

**Protection against Micro-organisms risk****Performance**

EN ISO 374-5



- \* Protection against bacteria and fungi
- \* Protection against viruses

Pass  
n/a

**Protection against Thermal risks****Performance**

EN 407



- \* Burning behavior
- \* Contact heat
- \* Convective heat
- \* Radiant heat
- \* Small splashes of molten metal
- \* Large quantities of molten metal

X  
Level 2  
X  
X  
X  
X  
X

**Protection against Cold****Performance**

EN 511



- \* Contact cold
- \* Convective cold
- \* Water penetration

Level 1  
X  
X